

Tolerances for extruded rubber products (SFS-ISO 3302-1)

Nominal dimension (mm)	Tolerances on cross-sectional dimensions of unsupported extrusions		
	Class E 1 (Silicon)	Class E 2 (EPDM)	Class E 3 (Cell rubber)
0 < a ≤ 1,5	± 0,15	± 0,25	± 0,40
1,5 < a ≤ 2,5	± 0,20	± 0,35	± 0,50
2,5 < a ≤ 4	± 0,25	± 0,40	± 0,70
4,0 < a ≤ 6,3	± 0,35	± 0,50	± 0,80
6,3 < a ≤ 10	± 0,40	± 0,70	± 1,00
10 < a ≤ 16	± 0,50	± 0,80	± 1,30
16 < a ≤ 25	± 0,70	± 1,00	± 1,60
25 < a ≤ 40	± 0,80	± 1,30	± 2,00
40 < a ≤ 63	± 1,00	± 1,60	± 2,50
63 < a ≤ 100	± 1,30	± 2,00	± 3,20

Nominal Length (mm)	Tolerances on cut length of extrusions		
	Class L 1	Class L 2	Class L 3
a ≤ 40	± 0,7	± 1,0	± 1,6
40 < a ≤ 63	± 0,8	± 1,3	± 2,0
63 < a ≤ 100	± 1,0	± 1,6	± 2,5
100 < a ≤ 160	± 1,3	± 2,0	± 3,2
160 < a ≤ 250	± 1,6	± 2,5	± 4,0
250 < a ≤ 400	± 2,0	± 3,2	± 5,0
400 < a ≤ 630	± 2,5	± 4,0	± 6,3
630 < a ≤ 1000	± 3,2	± 5,0	± 10,0
1000 < a ≤ 1600	± 4,0	± 6,3	± 12,5
1600 < a ≤ 2500	± 5,0	± 10,0	± 16,0
2500 < a ≤ 4000	± 6,3	± 12,5	± 20,0
a > 4000	± 0,16 %	± 0,32 %	± 0,50 %